

Motorized screen for ceiling or wall mounting. Professional quality at a low price. The Click-Mounting set allows for fast and easy installation on the wall or on the ceiling. An IR-receiver is integrated in the elegant, slim aluminium housing. A handheld remote control is included. An additional, wired IR-receiver is provided for in-concealed installation of the screen housing.

The very quiet Synchromotor and adjustable limit switches make the ElectricMaster II the ideal choice for most applications. The black rear surfaces and the black masking borders guarantee best contrast and full reflection of projection light. All screen surfaces are seamless.

Features

- Cost-effective motorized screen for wall- or ceiling mounting
- IR-receiver included in housing; IR-remote control included
- Additional, wired IR-receiver included for installations, where the screen's housing is out of the line of sight of the IR-remote.
- Small, elegant square bar housing, white coloured; aluminium
- Easy and quick installation
- Adapters for One-Click-Mounting included
- Very quiet Synchromotor
- Adjustable limit switches allow for the upper and lower end positions to be defined by presets
- Compact housing allows use in any application
- The Matte White screen surface with black borders is seamless
- HDTV-Formats and 16:10 come with additional black drop, which allows for the screen to be mounted in a standard eight foot ceiling to bring the screen to a comfortable viewing height.

Screen surface

MATTE WHITE

Specifications

Motorized projection screen, for wall-or ceiling mounting. Motor with integrated thermic overload protection and electric brake. Comes with connection cables and IR control. Housing: Aluminium base alloy, squared shape.

Housing colour: White.

Size of the projection surface is adjustable to any height. Upper and lower end position can be defined by presets. Projection surface with black masking borders.

Screen surface MATTE WHITE:

Matte white surface, fiber glass surface base material, washable, aging resistant, heavy duty materials, flame retardant.

Gain factor 1,0 - Viewing angle $\pm 50^\circ$

Dimensions: _____ x _____ cm, H x W;

Motor: 220 Volt, 50 Hz, 0,4 A


Manufacturer: COMM-TEC

Type: ElectricMasterII

Formats, Technical Details

	Format (cm) H x B	Cat.-Nr.	Housing length (cm)	Housing height (mm)	Housing width (mm)	Weight (kg)	Black masking border le/ri (cm)	Black masking border up/down (cm)
1:1 Standard – plus black masking borders								
70"	178 x 178	43FA-M070-070-IR	204	83	76	10,8	2,3	8/5
84"	203 x 203	43FA-M084-084-IR	234,4	83	76	12,4	5	8/5
4:3 Video – plus black masking borders								
84"	128 x 171	43FA-M084-IR	202,4	83	76	10,3	5	8/5
100"	152 x 203	43FA-M100-IR	234,4	83	76	12,5	5	8/5
120"	180 x 240	43FA-M120-IR	271,4	83	76	14,0	5	8/5
16:9 HDTV – plus black masking borders + 40cm black Drop								
92"	114 x 203	43FA-M092X-IR	234,4	83	76	11,8	5	40/5
106"	132 x 234	43FA-M106X-IR	264,8	83	76	13,3	5	40/5
136"	169 x 300	43FA-M136X-IR	332,4	126	119	33,6	5	40/8
16:10 – plus black masking borders + 55cm black drop								
94"	127 x 203	43FA-M094X-IR	235,1	85	81	12	5	55/5
109"	146 x 234	43FA-M109X-IR	267,4	85	81	13,5	5	55/5

Easy montage


Accessories (included in delivery)

- Wall-/ Ceiling mounting brackets
- Brackets for hanging mounting
- IR-Receiver built in
+ external IR Kit (cord included)
- IR-Remote control
- Power Cord with Plug

Accessories (optional)

- In ceiling mounting kit
 - for all dimensions
 - Slim ornament aluminium board in white
 - Service opening in the ceiling for maintenance
 - Fast and easy installation